



Learn more about
this product



Your Gateway to Efficient Connectivity

The Kvaser U100P-X1 is a robust, single-channel CAN/CAN FD to USB interface with reinforced galvanic isolation that squarely addresses the needs of the evolving automotive development market. Fully compatible with J1939, CANopen, NMEA 2000® and DeviceNet, this is the first in a new range of interfaces that is also suited to rugged applications in marine, industrial, heavy duty vehicle and heavy industries.



Warranty

2-Year warranty. See our general conditions and policies for details.



Support

Free support for all products by contacting support@kvaser.com



EAN

73-30130-01269-1

Major Features

- Supports CAN FD, up to 8 Mbit/s (with correct physical layer implementation).
- Supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers.
- Lightweight robust housing made of glass fibre reinforced polyamide overmolded with TPE.
- Intuitive LED UI.
- Reinforced Galvanic Isolation, 5000VAC rms applied for 60 seconds.
- 20 000 msg/s, each timestamped with a resolution of 1 μ s.
- Support for SocketCAN.
- IP67 rated housing.
- Compatible with J1939, CANopen, NMEA 2000® and DeviceNet. Higher layer protocol translation handled by the user's application. For software support please see our Technical Associates products and our Software Download page (www.kvaser.com).

Support

Documentation, Kvaser CANlib SDK and drivers can be downloaded for free at www.kvaser.com/downloads.

Kvaser CANlib SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, Visual Basic, Python and t programming language.

Kvaser CAN hardware is built around the same common software API. Applications developed using one device type will run without modification on other device types.



Technical Data

CAN Bit Rate	10 kbit/s to 1 Mbit/s
CAN Channels	1
CAN Transceivers	11898-2 Compliant
Certifications	CE, RoHS
Connector	J1939 Type-II
Current Consumption	Typical 250 mA
Dimensions	38 x 128 x 26 mm
Error Frame Detection	Yes
Error Frame Generation	Yes
Galvanic Isolation	Yes
MagiSync	Yes
Operating Systems	Windows, Linux
Silent Mode	Yes
Temperature Range	-40 to +85 °C
Timestamp Resolution	1 μ s
Weight	212 g



TDS Precision Products GmbH
Industriestrasse 1a
CH-8157 Dielsdorf

T + 41 44 885 30 80
info@tds-pp.com
www.tds-pp.com