_	8	1	7	6		5	*	4		3	I	2			1	
Γ	CATALOC	DYNAM	IC TORQUE							NOTES:						
	CATALOG CODE	NOMINAL	. TOLERANCE							1.		T DETERMI	NE FITNE	SS FOR	USE	
-		Nm	±%								IN APPLIC					
	PHA-0.28 PHA-0.37	0.28	35 30							2.		00 CYCLES R SPEEDS LE				
D	PHA-0.46	0.37	25							3.		D TO ACCE				D
	PHA-0.55	0.55	25								OR EQUIN	/ALENT.				
Ļ	PHA-0.65	0.65	25							[4]	HINGE DE	SIGNED TO AXIAL FOR			NNI	
											shown,	NOT DESIG	NED TO	SUPPO	RT	
_										5	MATERIAL	RCE IN THE	OPPOS		CIION.	_
										J.	ZINC BI	RACKET				
											ZINC SH HARDF	HAFT END NED STEEL	Shaft			
												NED STEEL		E ELEME	NT	
С																С
			CAT	ALO	G C(	DDE										
			Г	<b>'HA</b> - <u>}</u>	<u>^.//</u>											
																4
						Nm										
					- 0.28 - 0.37											
В					- 0.46 - 0.55											B
					- 0.65											
_																-
							TDS	Precision Products								_
							TDS Preci	sion Products GmbH	LEVEL DRAWN:		DESCRIPTION 16FEB11	PART NO:	DRAW	N DATE	APPROVED	-
							Industries CH-8157				TOLLDII	_				
Α							info@tds-				TOLLDII	TITLE:				A
							www.tds-	RPRET PRINT PER	REVISED: 0	<u>5MAY20</u>	<sup>dims:</sup> mm	SALI	es d	RAW	/ING	
							ASN THI	NE Y14.5M-1994 S PRINT IS THE DENTIAL PROPERTY		REE	LL	DESCRIPTION:			REV:	_
							OF REEL	L PRECISION MFG.	REFII			DESCRIPTION:	PH.	A	D	
	SPECIFICATIO								125	9 WILLOW LAKE B UL, MINNESOTA 5	OULEVARD		DO NOT SCALE		SHEET 1 OF 2	_
	8	I	/	6	I	5	T	4	I	3	I	2	I		1	

