


Data Sheet for Precision Resistors

Ultra Precise Metal Foil Resistor

Series MZH



- Temperature coefficient $<\pm 1$ ppm/°C @25°C
- Metal Foil Resistor with excellent long term stability
- Resistance range from 100Ω..100kΩ
- Ultra precise, resistance tolerances from $\pm 0,005\%$
- Hermetically sealed metal housing

Electrical Specification

Resistance range	100Ω..100kΩ
Resistance tolerance	$\pm 0,005\%$.. $\pm 1\%$
Power rating @ 70°C (0W @ +150°C)	0,3W
Max. working voltage	300V
TCR-rate	$<\pm 1$ ppm/°C @25°C
Working temperature range (max.)	-65..+150°C

Mechanical Specification

Resistance technology / material	Metal foil
Housing material	Metal (hermetically sealed)
Connections	Radial cooper tinned


Parameters	Test Conditions	Specification
Power Conditioning	25°C, rated voltage, 96 h	$\Delta R \pm 0,0025\%$
Short time overload	2,5 x rated voltage, 5 sec.	$\Delta R \pm 0,0025\%$
Life span (biased)	70°C, rated power,, 90 min. on 30 min off, 2000 h	$\Delta R \pm 0,01\%$
High temperature / humidity	+65°C..-10°C, 90..98% RH rated voltage, 10 cycles, 240h	$\Delta R \pm 0,0025\%$
Temperature shock	-65°C (30 min.), +150°C (30 min), 5 cycles	$\Delta R \pm 0,0025\%$
High temperature exposure	+150°C, no load 2000 h	$\Delta R \pm 0,01\%$
Solderability	245°C, 2 sec.	Coverage > 95%
Resistance to soldering heat	350°C, 3 sec.	$\Delta R \pm 0,0025\%$
Isolation resistance	500 VDC, 2 min.	>10.000MΩ
Dielectric strength	Atmo. Pres.: 300 VAC, 1 min.	$\Delta R \pm 0,0025\%$
Shock	100G, 6 ms, halfsine, X, Y, Z each 10 shocks	$\Delta R \pm 0,0025\%$
High frequency vibration	20G, 10Hz zu 2kHz zu 10Hz, 20 min. X, Y, Z each 2,5 h	$\Delta R \pm 0,0025\%$
Current noise		-42 dB

Data Sheet for Precision Resistors


Ultra Precise Metal Foil Resistor

Series MZH


Frequency Characteristics



Power Derating Curve




Temperature Characteristics



Temperature (°C)	ΔR/R (ppm)
-55	±40
0	±15
+25	±0
+50	±15
+125	±50

Temperature of the Resistor Surface




Data Sheet for Precision Resistors

Ultra Precise Metal Foil Resistor

Series MZH

Technical Drawing



Order code

Description

Selection: standard=black/bold, possible options=grey/cursive

Series:

MZH

Resistance tolerance:

±1%
±0,5%
±0,1%
±0,05%
±0,02%
±0,01%
±0,005%

W1%
W0,5%
W0,1%
W0,05%
W0,02%
W0,01%
W0,005%

Temperature coefficient: <±1 ppm/°C

TK0

Resistance value - please choose: From 100Ω to ≤ 100kΩ

xxxkxxx

Lead-Space:

3,81 mm
5,08 mm

3,81
5,08

Order Example	Series	Resistance tolerance	Temperature coefficient	Resistance value	Lead-Space
Choice	MZH	±0,1%	<1 ppm/°C	10,1kΩ	3,81
Code	MZH	W0,1%	TK0	10k100	3,81